



## Technical Data Sheet

### Attock Compressor Oil

**Attock Compressor Oil Series** is formulated with high quality paraffinic base oils and selected ash less additives. It is design to provide excellent protection to reciprocating and air compressors.

#### APPLICATIONS:

**Attock Compressor Oil Series** is suitable for the compressors where ash less antiwear R&O type lubricants are recommended. Attock Compressor Oil meet the DIN 51506, VDL.

#### BENEFITS:

- Reduce carbon deposit at cylinder head.
- Outstanding anti- wear properties.
- Excellent oxidation and thermal stability.
- Reduced deposit and extended service life.
- Excellent antifoaming and air release quality.

#### Typical Physical Characteristics:

PRODUCT	Compressor Oil		
	ASTM Methods	Compressor oil 100	Compressor oil 150
Appearance	Visual	Clear	Clear
Specific gravity at 60/60 °F	D 1298	0.892	0.894
Density at 85 °F	D 1298	0.883	0.884
Kinematics viscosity at 100 °C cSt	D 445	12.50	16.30
Kinematics viscosity at 40 °C cSt	D 445	105.62	156.1
Viscosity Index	D 2270	110	110
Flash point °C	D 92	230	250
Water by crackle test		Negative	Negative
Sulfated Ash mass %	D 874	Nil	Nil
Foaming Tendency	D 892	10/0, 10/0, 10/0	10/0, 10/0, 10/0
Pour point °C	D 97	-18	-18