



Technical Data Sheet

Attock Gold API CD/SD

Attock Gold is blended with selected mineral base Oils and additive package designed to provide protection to engines where monograde oils are recommended and to withstand hot climatic conditions.

APPLICATIONS:

Attock Gold is recommended for naturally aspirated Diesel engines. It can be used in gasoline engines where API SD grade is required. Attock Gold is particularly suited for use in mobile diesel power generators.

BENEFITS:

- Protect against varnish, sludge formation, acid and corrosion.
- Longer engine life.
- Longer Oil Service life.
- Reduced operating cost.

Typical Physical Characteristics:

PRODUCT	ASTM Methods	GOLD-50	GOLD-40
API		CD/SD	CD/SD
SAE		50	40
Appearance	Visual	Clear	Clear
Specific gravity at 60/60 °F	D 1298	0.898	0.896
Density at 85 °F	D 1298	0.889	0.887
Kinematics viscosity at 100 °C cSt	D 445	19.1	14.6
Kinematics viscosity at 40 °C cSt	D 445	221	148.4
Viscosity Index	D 2270	97	97
Flash point °C	D 92	245	245
Water by crackle test		Negative	Negative
TBN mg of KOH/gm	D 2896	5.2	5.1
Pour point °C	D 97	-12	-12