



## Technical Data Sheet

### Attock Hidrive Supreme API SL/CF SAE 20W-50

**Attock Hidrive Supreme** is a blend of superior selected base oils and advance additives. This product is a superior high performance multi-grade motor oil formulated to meet the requirements of modern passenger car engines requiring SAE 20W 50-viscosity rating.

#### APPLICATIONS:

Attock Hidrive supreme is recommended for use in passenger car engines including Gasoline and turbocharged Diesel engines. Attock Hidrive Supreme is well suited for hotter climatic conditions. It provides extra protection to moving parts of engine in high operating temperatures.

#### BENEFITS:

- Enhanced anti wear control, specifically in high performance engines.
- Enhanced engines deposit control.
- Enhanced high temperature oxidation control, which is necessary for engines operating under severe conditions at high temperature.
- Endurance against rust and corrosion
- Better and easy startup
- Improved control of volatility and oil consumption.

#### Typical Physical Characteristics:

PRODUCT	HIDRIVE SUPREME	
	ASTM Methods	HIDRIVE SUPREME
API		SL/CF
SAE		20W-50
Appearance	Visual	Clear
Specific gravity at 60/60 °F	D 1298	0.876
Density at 85 °F	D 1298	0.865
Kinematics viscosity at 100 °C cSt	D 445	17.50
Kinematics viscosity at 40 °C cSt	D 445	152.40
Viscosity Index	D 2270	125
Flash point °C	D 92	250
Water by crackle test		Negative
TBN mg of KOH/gm	D 2896	6.3
Pour point °C	D 97	-24