



Technical Data Sheet

Attock Gear PRO-5 85W-140 GL-5

Gear PRO-5 is made from high quality base oils and an additive system to provide excellent extreme pressure (EP) properties, wear resistance, oxidation stability, anti-rust and anti-corrosion qualities and protection against foaming. This lubricant provides excellent protection against shock loading as well as protection for the sealing materials.

APPLICATIONS:

Gear PRO-5 is recommended for use in where the lubricant manufacturers specify API GL-5. This product may be used in the manual transmissions of passenger cars, light trucks or high performance cars. Manufacturers' recommendations should be followed as to SAE grade and ambient temperature.

BENEFITS

- Excellent extreme pressure properties.
- Outstanding thermal and oxidation stability.
- Protect against rust and corrosion.
- Compatible with typical automotive seals and gaskets.
- Effective low temperature lubrication.
- Exceptional load carrying ability.

Typical Physical Characteristics:

PRODUCT	GEAR PRO-5	
	ASTM Methods	GEAR PRO-5 85W-140
API		GL 5
SAE		85W-140
Appearance	Visual	Clear
Colour	D 1500	L 4.5
Specific gravity at 60/60 °F	D 1298	0.908
Density at 85 °F	D 1298	0.899
Kinematics viscosity at 100 °C cSt	D 445	26.80
Kinematics viscosity at 40 °C cSt	D 445	362.44
Viscosity Index	D 2270	99
Flash point °C	D 92	230
water by crackle test		Negative