



Technical Data Sheet

Attock Compressor oil

Attock Compressor Oils is formulated with high quality paraffinic base oil and with selected ash less additive. It is design to provide excellent protection to reciprocating and air compressors.

APPLICATIONS:

Attock Compressor Oils is suitable for the compressors where recommended ash less antiwar R&O type lubricants. Meet the DIN 51506, VDL.

BENEFITS:

- Reduce carbon deposit at cylinder head.
- Outstanding anti- wears properties.
- Excellent oxidation and thermal stability.
- Reduced deposit and extend service life.
- Excellent antifoaming and air release quality.

Typical Physical Characteristics:

PRODUCT	ASTM Methods	Compressor Oil		
		Compressor oil 68	Compressor oil 100	Compressor oil 150
Appearance	Visual	Clear	Clear	Clear
Specific gravity at 60/60 °F	D 1298	0.892	0.892	0.894
Density at 85 °F	D 1298	0.883	0.883	0.884
Kinematics viscosity at 100 °C cSt	D 445	9.20	12.50	16.30
Kinematics viscosity at 40 °C cSt	D 445	68.90	105.62	156.1
Viscosity Index	D 2270	110	110	110
Flash point °C	D 92	224	230	250
Water by crackle test		Negative	Negative	Negative
Sulfated Ash mass %	D 874	Nil	Nil	Nil
Foaming Tendency	D 892	10/0, 10/0, 10/0	10/0, 10/0, 10/0	10/0, 10/0, 10/0
Pour point °C	D 97	-18	-18	-18